

DIAMOND

ACRYLIC FLOOR POLISH (25%)

- *High quality shine for improved appearance*
- *Thermoplastic polymer protects the floor*
- *Builds good slip-resistance - no health and safety concerns*



A high quality acrylic polymer-based metallised floor polish, which dries to a high level deep gloss (Drybright), with excellent slip resistance.

USES

Diamond protects and prolongs the life of flooring materials. It is a super high solids polish that produces a low maintenance, durable finish.

Suitable for use on non-porous floors, including; vinyl, thermoplastic, linoleum, rubber, asphalt, sealed wood, marble and terrazzo.

Possible areas of use include hospital corridors and wards, schools, offices, shops, airports, village halls, etc.


DIRECTIONS

PREPARATION: To obtain optimum results, it is important that thorough preparation of the floor is undertaken. The floor must be thoroughly cleaned to remove all dirt, grease and old polish films by using a quality polish remover such as Clover Chemicals' REMOVE or ZIP STRIP. The floor must be well rinsed with water and allowed to dry before applying DIAMOND.


APPLICATION: Apply a thin film of DIAMOND (undiluted) using a mop or polish applicator. Drying time is normally around 30 minutes. Apply a second coat and allow to dry. Coverage is dependent on the porosity of the floor covering. In general, 5 litres of DIAMOND will cover approximately 250 square metres of floor.




Code: 101




Linoleum




PVC/Vinyl




Rubber



Laminate



Sealed wood



Marble

pH in use



PACK SIZES



5L



CLOVER CHEMICALS LTD 
WHALEY BRIDGE, HIGH PEAK, SK23 7DQ.
TEL: +44 (0)1663 733114 FAX: +44(0)1663 733115
www.cloverchemicals.com