Product Specification Sheet



C503 PROSHINE

LABEL INSTRUCTIONS

Product Description & Directions for Use:

A high solids metallised 'dry-bright' floor finish formulated to give a long lasting deep gloss shine on vinyl, linoleum, thermo-plastic, rubber, sealed wood, cork, concrete, asphalt, terrazzo and other non-porous smooth floors coverings.

For professional and industrial use only.

Proshine is ready-to-use. Do not dilute with water.

Do not shake container.

Ensure floor is clean, dry and free from all residues. Semi-porous, concrete and impoverished floors should be sealed with a base coat of Proseal. Spread Proshine evenly using a slightly damp mop or polish applicator. Apply 2 or 3 very thin coats, allowing 30 to 60 minutes between coats. Do not over apply. Coverage is approximately 250 m² per 5L per coat. Allow final coat to dry completely before re-use. Do not buff floor at this stage. Periodically the floor gloss can be maintained by spray buffing with Protreat.

Keep from freezing.



- Contains 25% polymer for a long lasting deep slip resistant shine.
- Two or three thin coats are recommended for best results.
- White emulsion with acrylic odour.
- Coverage approx. 250m² per 5 litres per coat.

pH Concentrate: 9.0 pH Diluted: Not applicable

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

Wear protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice / attention.

Safety data sheet available on request.

Contains triisobutyl phosphate. May produce an allergic reaction.

Please consult the Safety Data Sheet before using this product.

This product is intended for professional use only. The information given is intended to be of assistance to users but is without guarantee. Variations can occur in application and users are advised to conduct their own tests. Suggestions for use neither give nor imply any guarantee as to the intended use.

Product Name: PROSHINE Product Code: C503

Manufacturer: Prochem Europe Ltd., Oakcroft Road, Chessington, Surrey KT9 1RH, UK.

Telephone No: 020 8974 1515 (UK) +44 20 8974 1515 Website: www.prochem.co.uk Email: sales@prochem.co.uk



Issue Date: 21/10/2014