

TAR AND GLUE REMOVER

Page: 1

Compilation date: 01/08/2009

Revision date: 27/03/2015

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TAR AND GLUE REMOVER

Product code: 704

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: Clover Chemicals Ltd

Clover House

Macclesfield Road

Whaley Bridge, High Peak

Derbyshire SK23 7DQ

UK

Tel: +44 (0) 1663 733114 **Fax:** +44 (0) 1663 733115

Email: technical@cloverchemicals.com

1.4. Emergency telephone number

Emergency tel: NHS Direct 08454647

NHS24 0845242424

ROI 018092166

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304

Most important adverse effects: May be fatal if swallowed and enters airways.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

Signal words: Danger

Hazard pictograms: GHS08: Health hazard

TAR AND GLUE REMOVER

Page: 2



Precautionary statements: P102: Keep out of reach of children.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P315: Get immediate medical attention.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PETROLEUM DISTILLATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-149-8	64742-47-8	-	Asp. Tox. 1: H304	>90%

3 - BUTOXYPROPAN - 2 - OL

225-878-4	005131-66-8	_	Skin Irrit. 2: H315; Eve Irrit. 2: H319	1-10%
220 070 1	000101 00 0		Okiii iiiii. 2. 11010, Eyo iiii. 2. 11010	1 10 /0

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin. Drench the affected skin with running water for 10

minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to

drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain

may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

TAR AND GLUE REMOVER

Page: 3

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking

containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do

not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is

forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources

of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting

and electrical equipment are not a source of ignition.

Suitable packaging: Stainless steel. Aluminium containers. Polyethylene.

7.3. Specific end use(s)

Specific end use(s): No data available.

TAR AND GLUE REMOVER

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PETROLEUM DISTILLATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000 mg/m3	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. **Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Gloves (solvent-resistant).

Eye protection: Safety glasses. Ensure eye bath is to hand.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Benzene.

Viscosity: Non-viscous

Boiling point/range°C: 171-280 Melting point/range°C: <0

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 63 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.834 pH: non aqueous

VOC g/I: 834

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

TAR AND GLUE REMOVER

Page: 5

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Flames.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

3 - BUTOXYPROPAN - 2 - OL

ORAL	RAT	LD50	2700	mg/kg	
0. u .=			• •		

Relevant hazards for substance:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain

may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

TAR AND GLUE REMOVER

Page: 6

3 - BUTOXYPROPAN - 2 - OL

-	48H EC50	>1000	mg/l
GUPPIES	96H LC50	560-1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Floats on water. Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

Phrases used in s.2 and s.3: H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

TAR AND GLUE REMOVER

Page: 7

shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.