TERRA-COAT

LOW GLOSS FLOOR POLISH



www.cloverchemicals.com

- Low gloss / Low glare finish
- Tough durable polymer protects the flooring
- One coat for perfect results

A tough water based polymer emulsion that dries to a low gloss finish.

Terra-Coat produces a modern low gloss coating on hard floors, that protects and enhances the original flooring.

USES

For interior use only.

Perfect in areas where 'no burnishing' is required.

Suitable for use on non-porous floors including - vinyl, thermoplastic, linoleum, rubber, sealed wood, marble and terrazzo.

DO NOT use on surfaces that have been oiled or waxed.

Not suitable for absorbent stone, terracotta or glazed ceramic tiles.

NOT for exterior (outside) use.

PREPARATION

To obtain optimum results, it is important that thorough preparation of the floor is undertaken. The floor must be thoroughly cleaned to remove all dirt, grease and old polish films.

First brush the floor to remove debris.

Use a quality polish remover such as *Remove* or *Zip-Strip* from CLOVER CHEMICALS, to clean and prepare the floor, removing polish coatings.

APPLICATION

Pour Terra-Coat into a clean plastic bucket.

Apply a generous film of Terra-Coat to the floor from the bucket using a new, clean Kentucky mop or polish applicator.

Terra-Coat will dry in 30-60 minutes however allow it to harden for a minimum of 6 hours before allowing traffic back on the floor.

SECOND COAT/MULTIPLE COATS:

A second coat will reduce the matte effect, may not coat evenly and may leave streaks.

Always leave each coat to dry for 24 hours before applying another coat.

Always coat a small test area to determine that the result is satisfactory before coating the whole area.

COVERAGE

Coverage varies depending on the porosity of the floor.

5 Litres of Terra-Coat will cover approximately 100 square metres of floor in one coat.

MAINTENANCE

Sweep the floor daily.

Clean the floor with a neutral cleaner (eq. Floorit, Impact, DD10) using a mop or

DO NOT buff, burnish or spray clean as this will produce a glossy finish.

REMOVAL

Use **CLOVER** floor polish strippers.

Code: 117

Linoleum



PVC/Vinyl




Rubber



Sealed wood



Marble







Clover House | Macclesfield Road | Whaley Bridge | High Peak | SK23 7DQ Tel: +44 (0)1663 733 114