

Superseal™

Polyurethane floor seal



Solvent based, polyurethane floor seal for use on internal wood & concrete floors.

Dries to a tough, very durable & slip resistant, high gloss finish.

Extremely hard wearing, impervious to grease, soil & moisture.

- Provides a protective barrier that prolongs the life of the floor surface.
- Enhances the natural colour of wood.
- Suitable for heavy traffic areas.
- Coverage per 5 litres - up to 25 sq. metres for 2 coats.
- One pack product, no additional hardener required VOC 460 g/litre.

SEALING FLOORS:

Apply to a new or untreated wooden floor. Alternatively remove existing seal & ensure floor is clean & dry.

Use undiluted.

Apply two or three thin coats with seal applicator or a clean soft brush.

Allow each coat to dry for 8 hours, although 24 hours is preferable.


Additional coats can be applied if required. Sanding in between coats is not necessary, but a light sand with a medium grade floor pad will help key the surface if a 3rd or 4th coat is applied.

After the final coat, leave for 24 hours before subjecting to traffic, 24 hours before cleaning & 7 days before applying emulsion floor polish.

DO NOT apply to new concrete floor, allow 6 months for moisture to evaporate & avoid the possibility of the seal flaking.

RELATED ITEMS:

- Sealaqua - Water based polyurethane floor seal.
- Floor & Carpet Care Guide.



5l

Order Code: A027TEV

Pack: 1 x 5 litre (4.79 kg)

Pallet: 120 Packs

PRODUCT INFORMATION:

Appearance:	Clear amber semi-viscous liquid
Odour:	Characteristic of white spirit
pH - undiluted:	N/A
Shelf life:	3 years

COMPOSITION:

Contains a blend of low aromatic white spirit & alkyd modified polyurethane resin.

BIODEGRADABILITY:

All surfactants used in Evans Vanodine products comply with the current European Regulations concerning biodegradability & protection of the environment.

QUALITY ASSURANCE:

EVANS VANODINE INTERNATIONAL PLC operates under an ISO 9001 Quality Management System Cert. No. FM 09535 and an ISO 14001 Environmental Management System Cert. No. EMS 506072 registered by the British Standards Institution.

REVISION DATE:

01/06/16



Evans Vanodine International plc

Brierley Road, Walton Summit, Preston, PR5 8AH, UK

www.evansvanodine.co.uk | Tel: +44 (0)1772 322200 | Fax: +44 (0)1772 626000



ISO 9001
Quality
Management

ISO 14001
Environmental
Management

