K003 : SELFREEZ

chewing gum and sticky substance remover for easy removal from carpets and floors

Description of product

Also suitable for the removal of sticky deposits. Rapidly freezes chewing gum and sticky deposits so that they may be guickly and easily scraped from carpets and furnishings. Freezes down to -80°C. Will not attack fabrics or plastics. Many uses in electronics and components assembly and testing.

Directions

DIRECTIONS: 1. Spray onto sticky substance. 2. Scrape off with a knife when white frost hardens it. 3. If substance softens before removed completely, repeat the above directions. N.B. Use spray at least 15cm from exposed skin, extended spray release may result in cold injury from the can.

iNsight Supported

Environmental Profile

Biodegradability

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit http://www.selden.co.uk/insight

iNsight recommended product uses Carpet - chewing gum removal Special - chewing gum removal



n/a

see label

Selden Environmental Charter

. If it can be recycled, it will be recycled.

· Conserving energy, preserving resources.

. By being innovative, we strive to do better. . We like to work in partnership with our clients.

Visit our website for more information

. We set ourselves industryleading standards.

· Selden minimises wastage, packaging and transportation.

· Our chemicals policy exceeds regulatory requirements.

. We don't expect other people to clean up after us.

R12 Extremely flammable.

A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use., A2 Do not spray on a naked flame or any incandescent material., S23 Do not breathe vapour/spray., S51 Use only in well-ventilated areas. S2 Keep out of the reach of children.

Technical Data

Composition Hydrochlorofluorocarbor

- 0.714 Density
- Stability Two years minimum
- Storage Pressurised container. Store out of direct sunlight. Temperature must not exceed 50oC

Aerosol Information

Propellant Hydrofluorocarbon Pressure 100 psi Spray Rate 1.4



UKAS accredited testing laboratory No. 4204



SELDEN formulating testing manufacturing the highest

standards

Selden Research Limited Staden Business Park, Staden Lane, Buxton Derbyshire, SK17 9RZ Tel: 01298 26226 | Fax: 01298 26540 | Email: info@selden.co.uk | web: www.selden.co.uk







EXTREMELY FLAMMABLE Risk Phrases

Safety Phrases

External Accreditations

18001 - Health & Safety System

14001 - Environmental System

IPPC Certified Manufacturer

9001 - Quality System

COSHH+ Supported Selden's bespoke COSHH awareness and product Sustainability training tool. Users specify the products in use and Product conforms with the instantly generate a full training pack to enable quick DEFRA endorsed and effective staff training. Sustainable Cleaning quidance

www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages





