Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PROXL - SANITIZE FOAM SANITIZER (500ML)

- Article number: HEAPSF70500

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Surface cleaning
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

CAPELLA SOLUTIONS GROUP

1 MANTLE CLOSE

OFF BINGHAM ROAD SITTINGBOURNE, KENT, ME10 3BW

Tel: +44 (0)1634 823900

Fax:

- · Further information obtainable from: Research & Development: sales@capellasolutionsgroup.com
- 1.4 Emergency telephone number: During normal business hours: Tel: +44 (0)1634 823900

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS05 corrosion

Skin Corr. 1 H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS05

#### · Signal word Danger

#### Hazard-determining components of labelling:

tetrasodium ethylenediaminetetraacetate

Alcohols, C12-18, ethoxylated

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

(Contd. on page 2)

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

#### Trade name: PROXL - SANITIZE FOAM SANITIZER (500ML)

(Contd. of page 1)

P260 Do not breathe spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

10.074 % by mass of the contents are flammable

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· **Description:** Active substance with propellant

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 5131-66-8 EINECS: 225-878-4 Reg.nr.: 01-2119475527-28	3-butoxypropan-2-ol Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<2.5%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	1-<2.5%
CAS: 64-02-8 EINECS: 200-573-9 Reg.nr.: 01-2119486762-27	tetrasodium ethylenediaminetetraacetate Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332	1-<2.5%
CAS: 68213-23-0 Reg.nr.: 01-2119489387-20	Alcohols, C12-18, ethoxylated Eye Dam. 1, H318	1-<2.5%
CAS: 1336-21-6 EINECS: 215-647-6 Reg.nr.: 01-2119488876-14	ammonia Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; STOT SE 3, H335	≥0.25-<1%
CAS: 7173-51-5 EINECS: 230-525-2 Reg.nr.: 01-2119945987-15	didecyldimethylammonium chloride  Acute Tox. 3, H301; Skin Corr. 1B, H314; Eye Dam. 1, H318;  Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411	≥0.1-<0.25%
Additional information:		

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

### Trade name:PROXL - SANITIZE FOAM SANITIZER (500ML)

(Contd. of page 2)

Immediately rinse with water.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

#### **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:** 

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

(Contd. on page 4)

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

Trade name; PROXL - SANITIZE FOAM SANITIZER (500ML)

(Contd. of page 3)

Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

34590-94-8 Dipropylene glycol monomethyl ether

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

Trade name:PROXL - SANITIZE FOAM SANITIZER (500ML)			

• 9.1 Information on basic physical and chemical properties	
General Information	

· Appearance:

Form: Aerosol

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· pH-value at 20 °C: 12.6

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 100 °C

-97 °C · Flash point:

Flammability (solid, gas): Not applicable.

**Auto-ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

1.1 Vol % Lower: 14 Vol % Upper:

· Vapour pressure at 20 °C: 4000 hPa

**Density:** Not determined. · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not applicable.

· Solubility in / Miscibility with

Not miscible or difficult to mix.

1.6 %

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined **Kinematic:** Not determined.

· Solvent content:

**Solids content:** 

9.8 % **Organic solvents:** 86.0 % Water:

(Contd. on page 6)

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

Trade name: PROXL - SANITIZE FOAM SANITIZER (500ML)

(Contd. of page 5)

### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

# 5131-66-8 3-butoxypropan-2-ol

Oral LD50 2124-2700 mg/kg (Rat)
Dermal LD50 >2000 mg/kg (Rat)

- Primary irritant effect:
- Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

### 5131-66-8 3-butoxypropan-2-ol

LC50 (96h) 560-1000 mg/l (Fish)

LC50 >1000 ug/l (Daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

#### Trade name: PROXL - SANITIZE FOAM SANITIZER (500ML)

(Contd. of page 6)

• 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP3 Flammable

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

<b>SECTION 14</b> :	Transport	information
DECTION	TIGHSPOIG	

. 14 1	<b>UN-Number</b>
14.1	Ulistinuliidei

· ADR, ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR, ADN UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· ADN

· ADN/R Class: 2 5F

· IMDG, IATA



· Class 2.1 · Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

Hazard identification number (Kemler code):

• EMS Number: F-D,S-U
• Segregation groups Alkalis

• Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

• Segregation Code SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from" class 1

(Contd. on page 8)

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

#### Trade name: PROXL - SANITIZE FOAM SANITIZER (500ML)

	(Contd. of page	
	except for division 1.4.	
	For AEROSOLS with a capacity above 1 litre:	
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:	
	Segregation as for the appropriate subdivision of class 2.	
14.7 Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
· ADR		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	
1 1 ( )	Not permitted as Excepted Quantity	
Transport category	2	
Tunnel restriction code	D	
· IMDG		
· Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Regulation (EU) No 649/2012

7173-51-5 didecyldimethylammonium chloride

Annex I Part 1

· National regulations:

Class	Share in %
Wasser	75-<100
NK	2.5-<10

- · VOC-CH 9.78 %
- · VOC-EU 97.8 g/l
- Danish MAL Code 5-6
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

(Contd. on page 9)

Printing date: 10.04.2020 Version: 2 Revision: 10.04.2020

#### Trade name: PROXL - SANITIZE FOAM SANITIZER (500ML)

(Contd. of page 8)

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

# · Department issuing SDS: Research & Development

#### · Contact:

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 3: Acute toxicity - oral - Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Corr. 1: Skin corrosion/irritation - Category 1

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aguatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GB